

MOBILE PLATFORM

Replacing ladders in facilities everywhere

COMPACT SERIES

Elevated operator platform for easier access to work areas Proven reliability on both concrete floors and mesh decks Narrow wheel base for easy navigation in virtually any walkway Intuitive handlebar steering for a familiar driving experience Engineered to distribute weight and prevent tipping Auto-engaging electromagnetic braking system for sure stopping Overnight charging provides a full-day's operation in most settings Convenient floor chute* and front basket for maximum productivity



Slim design to drive through the narrowest of walkways



Included off-board charger for easy overnight charging



Freewheel feature allows rolling when powered down



- Handlebar-style drive console includes:
- Keyed power on (two keys included)
 - Turn-to-steer with multiple hand positions
 - Forward throttle (right-hand side)
 - Reverse throttle (left-hand side)
 - Maximum speed control dial
 - LED multi-level battery gauge
 - Push-button horn



SPECIFICATIONS

Unit Weight: 145 lbs.
Weight Capacity: 300 lbs.
Max Speed: 4 mph
Max Incline: 12°
Turning Radius: 43"
Ground Clearance: 2"

Tires: Solid rubber (front 7"x2", rear 8"x2")
Motor: Direct drive with differential
Brakes: Auto-engaging electromagnetic
Batteries: 24v system (two 12v 21ah batteries)
Charger: 2 amp (off board)
*Floor Chute: Model CP2032 only

DIMENSIONS

CP2022: Standing platform 22"H, overall 42"L x 20"W x 65"H
CP2032: Standing platform 32"H, overall 42"L x 20"W x 75"H

US GLOBAL RESOURCES

Toll-free: 888-334-1440
Texas: 830-755-4768
Email: usgr@usgr.com | www.usgr.com

