

# The TC-275 S/C Incinerator

**\$10,800**

## Features

275 Lb capacity  
Only requires 10' x 10'  
space Natural or Propane  
Fuel or Oil Two re-  
adjustable gas burners  
Thermocouple installation to conserve  
fuel 115 Volt  
Inside or outside  
installation Only 2% ash  
remains  
3 inches of 3000 degree refractory  
lining 2 inches of refractory lining in  
the stack  
Counter-balanced charge door with 4"  
3000 degree refractory lining

## Space and Volume Efficient

The TC 275 S/C is the incinerator that sets the standard for efficiency. Designed with limited space in mind the TC 275 S/C requires only a 10' x 10' area for operation to handle up to a 275 pound capacity. A weather-proof electrical control box means that the TC 275 S/C can be installed indoors or out.

## Energy Efficient

Two re-adjustable gas burners with a pre-set burn cycle time and a thermocouple installation conserves fuel and makes the TC 275 S/C very energy efficient. Also, the use of fresh air to complete the destruction of refuse saves 50% or more over old-type burning methods. Natural, propane or oil fuel may be used.

## Anti-Polluting

The TC 275 S/C has less smoke and odor than most incinerators and only 2% ash to remove.

U.S. Environmental tests are available upon request.



**U.S. GLOBAL RESOURCES**

*80 YEARS OF SERVICE TO A GROWING WORLD*

## Electrical & Gas Specifications

- Customer to connect power and gas to unit.
  - Customer also to furnish pad for incinerator.
  - **Power:** 115V
  - **Natural Gas:** 5" to 8" W.C. gas pressure/ Minimum 1-1/2" gas pipe
  - **LP Gas:** Low pressure. Minimum 1/2" gas pipe.
- Oil Gas**

## Warranty

All materials and workmanship used in the construction of its incinerator and the refractory are guarantees for a one year period from the date of installation. All purchased electrical parts such as burners, fans, timers, and other controls will carry the applicable manufacturer's guarantee of 90 days. Seller shall not be liable for any injury or damages to person or property or any other incidental or consequential damages.

### Specifications

- **Height:** 9'1" **Length:** 5'8" **Width:** 4'1"
- **Weight:** 4,000 lbs
- **Metal:** 11 gauge
- **Lining:** 3" 3000° refractory
- **Charge Door:** 14.5" x 24" . Lining: 2" 3,000° refractory
- **Stack:** 4' Sparkscreen: 6" Stainless Steel 2" refractory lining
- **Ash Door:** 4" x 6" **Lining:** 4" 3000° refractory
- **Grates:** 1/2" x 2" x 20"
- **Burners:** 100,000 BTU incinimite with cover. 50,000 BTU Second Chamber burner with cover.
- **Clean-out Rod:** 54" long
- **Two Timers:** 60 minute

### Guarantee

Every unit built is constructed of the highest quality materials and built by skilled technicians. Every incinerator bear the assurance of long life and trouble-free operation



# US GLOBAL RESOURCES

80 YEARS OF SERVICE TO A GROWING WORLD



**U.S., CANADA & INTERNATIONAL SALES**

Toll-free: +1 (888) 334-1440 | +1 (830) 755-4768 | Fax: 830-755-4753

Email: [usgr@usgr.com](mailto:usgr@usgr.com) | Website: [www.usgr.com](http://www.usgr.com)