

# The TC-275 Incinerator

**\$7,900**

## Features

- 275 Lb capacity
- Only requires 10' x 10' space
- Natural or Propane Fuel or Oil
- One re-adjustable gas burner
- Thermocouple installation to conserve fuel
- 115 Volt
- Inside or outside installation
- Only 2% ash remains
- 3 inches of 3000 degree refractory lining
- 2 inches of refractory lining in the stack
- Counter-balanced charge door with 4" 3000 degree refractory lining

## Space and Volume Efficient

The TC 275 is the incinerator that sets the standard for efficiency. Designed with limited space in mind the TC 275 requires only a 10' x 10' area for operation to handle up to a 275 pound capacity. A weather-proof electrical control box means that the TC 275 can be installed indoors or out.

## Energy Efficient

One re-adjustable gas burner with a pre-set burn cycle time and a thermocouple installation conserves fuel and makes the TC 275 very energy efficient. Also, the use of fresh air to complete the destruction of refuse saves 50% or more over old-type burning methods. Natural, propane or oil fuel may be used.

## Anti-Polluting

The TC 275 has less smoke and odor than most incinerators and only 2% ash to remove. U.S. Environmental tests are available upon request.

## Electrical & Gas Specifications

- Customer to connect power and gas to unit.
  - Customer also to furnish pad for incinerator.
  - **Power:** 115V
  - **Natural Gas:** 5" to 8" W.C. gas pressure/ Minimum 1-1/2" gas pipe
  - **LP Gas:** Low pressure. Minimum 1/2" gas pipe.
- Oil Gas**



**U.S. GLOBAL RESOURCES**  
*OVER 75 YEARS OF SERVICE TO A GROWING WORLD*

## Warranty


All materials and workmanship used in the construction of its incinerator and the refractory are guaranteed for a one year period from the date of installation. All purchased electrical parts such as burners, fans, timers, and other controls will carry the applicable manufacturer's guarantee of 90 days. Seller shall not be liable for any injury or damages to person or property or any other incidental or consequential damages.

## Specifications

- **Height:** 7'10" **Length:** 5'8" **Width:** 4'1"
- **Weight:** 3,200 lbs
- **Metal:** 11 gauge
- **Lining:** 3" 3000° refractory
- **Charge Door:** 14.5" x 24" . Lining: 2" 3,000° refractory
- **Stack:** 4' Sparkscreen: 6" Stainless Steel 2" refractory lining
- **Ash Door:** 4" x 6" **Lining:** 4" 3000° refractory
- **Grates:** 1/2" x 2" x 20"
- **Burners:** 100,000 BTU incinimite with cover. 50,000 BTU Second Chamber burner with cover.
- **Clean-out Rod:** 54" long
- **Timer:** 6 hour

## Guarantee

Every unit built is constructed of the highest quality materials and built by skilled technicians. Every incinerator bears the assurance of long life and trouble-free operation



# U.S GLOBAL RESOURCES

Toll-free: 888-334-1440

Texas: 830-755-4768 • Seattle: 206-722-3999 Fax: 206-721-1140 / 830-755-4753

Email: [usgr@usgr.com](mailto:usgr@usgr.com) • Website: [www.usgr.com](http://www.usgr.com)